

## Privacy Frost Window Film Instructions

### A simple and affordable DIY privacy system

Easyfix Privacy Frost Window Film is a quick and easy solution for your privacy needs. It is for indoor use and can be fitted to your existing glass windows for a permanent solution or you can fit it on your secondary glazing sheet should you wish to be able to remove and replace it when desired.

#### Ordering your Privacy Frost

The film is cut from a roll 1220mm wide so if your window is over that in height or width then you will need to order the appropriate length of film to cover the greater dimension. If you order 4 x 500mm pieces we will provide one piece 1220mm x 2000mm.

#### Kit required

Squeegee blade, glass scraper, sharp knife (our mini-installation kit), plus sharp scissors, tape measure, spare store card, towel and a spray bottle. Put a couple of drops of washing up liquid in the bottle and top up with water.

#### Fitting Easyfix Privacy Frost on existing glass windows

1. Trim down the Privacy Frost Film so you have roughly 20mm excess on each dimension. This will make it easier to handle when fitting.
2. Clean the window thoroughly using the soapy solution and a glass scraper to remove any specks of paint /dirt as well as any other stickers or coverings.
3. Wet the entire area you wish to cover with the soapy solution. It may be worth placing a towel below the window to absorb the excess.
4. Lay the film face down on a flat surface and peel back a small amount of the Privacy Frost liner to reveal the adhesive side and spray it with the soapy solution.
5. Spray your fingers to hold the Privacy Frost while gradually peeling back the liner and spray the adhesive side liberally as you remove the Liner.
6. Align the top edge and one side into position starting from the corresponding corner and then smooth the rest of the film into place.
7. Spray the entire face of the Privacy Frost film with the soap solution to act as a lubricant for squeegeeing.
8. Starting from the fitted corner squeeze out the solution using the Felt Edged Squeegee from top to bottom and then side to side.
9. Use a store card to guide the retractable blade along the edges that require trimming and then squeegee those edges again to ensure all the solution between glass and film has been removed.
10. Check both sides for air bubbles, if possible, and if more squeegeeing is required remember to lubricate the face of the film again before doing so.

#### Fitting Easyfix Privacy Frost on Secondary panes

The principle for fitting to the secondary glazing sheet is the same but you may find it easier to fit the film with the sheet laid flat and you will need to replace the steps laid out below in instructions above:

2. If applying to Polycarbonate sheet they should be clean once the protective film is removed but it is worth wiping over with Anti Static Spray to ensure the static charge is dissipated along with any dust/hairs attracted while removing the protective film.
6. Cover the entire secondary glazing sheet with a little film overlapping each edge.
9. Turn the sheet over and trim the excess using the edge of the sheet as the guide.
11. Fit the Secondary glazing sheet as normal.



**PLEASE READ INSTRUCTIONS THOROUGHLY BEFORE CUTTING OR FITTING ANY SYSTEM**

If you would like to share a picture of your installation then please email it to [sales@secondarydiyglazing.com](mailto:sales@secondarydiyglazing.com)

TUBEWAY (SALES) LIMITED, Elton Park, Hadleigh Road, Ipswich, IP2 0HN. Tel: 01473 261126

Buy online at [www.secondarydiyglazing.com](http://www.secondarydiyglazing.com) email: [sales@tubeway.co.uk](mailto:sales@tubeway.co.uk) website: [www.tubewaysales.com](http://www.tubewaysales.com)

EASYFIX® is a Registered Trademark of Tubeway (Sales) Limited - Apr23